

### Head Office

Unit 12, 8 Leighton Place  
Hornsby  
NSW, 2077  
Australia

### Firefly Office

P.O BOX 52  
Laidley  
QLD, 4341  
Australia

### Contact details

Phone: (07) 5411 4209  
Mobile: 0400 966 899  
Email: [trevor@tbafirefly.com.au](mailto:trevor@tbafirefly.com.au)



In accordance with AS3959-2009, homes that are to be built in areas designated as BAL-40 the Fascia element of construction needs to have passed AS1530.8.1 or alternatively a product that has passed the higher test standard AS 1530.8.2 may be used to satisfy all lower BAL's

Noggin out between the rafters ensuring the noggins are flush to the top and bottom of the crown ends. (Noggins can be 3" X 2" timber or 70mm steel partition track).



Mechanically fix the Firefly Plus 60 to the noggins using 25mm X 0.6mm steel hoop iron using 32mm drywall screws @ 100mm centres.

Overlay the top and front of the Firefly Plus 60 with Intubatt FZ. Adhere all joints with Intucoat Mastic and screw fix through the Intubatt FZ and Firefly Plus 60 into the timber noggins using 70mm drywall screws and penny washers @ 600mm centres.



# BAL-40 FASCIA SYSTEM

# BAL-40 FASCIA SYSTEM



Overcoat all joints, edges and screw/washer heads with Intucoat mastic ensuring a sea of white and no gaps on completion.

Lay sarking over the top of the Intubatt FZ ensuring ample overlap is left around the perimeter. Once the gutter is installed the sarking can be trimmed to length allowing the standard 50mm lap into the gutter. Overlay the top of the sarking, directly above the Intubatt FZ with 160mm wide x 100 high Firefly Party Wall Batt. When the steel roofing sheets are installed, the Firefly party wall batt will squash up into the profile of the steel sheeting, creating a secure seal against flame and ember attack.

